

Tabla de Selección para Bombas para Aguas Negras (Sólidos 2")

Serie	Modelo	No. de Parte	Desc.	HP	Volts	Amps.	Rendimiento GPM @ Pies					Valvula Cerrada		Cable (MTS)	Peso (KG)	Uds/ Caja
							5'	10'	15'	20'	30'	PIES	PSI			
9SN	9SN-CIM	509203	2" F	4/10	115	9	110	75	30	0	0	20	8,7	6	16	1
10SN	10SN-CIM	511322	2" F	1/2	115	9,5	120	95	70	30	0	25	10,9	6	16	1
	10SN-CIM	511328	2" F	1/2	230 / 1	4,5	120	95	70	30	0	25	10,9	6	16	1
WS102	WS102M-12	620203	2" F	1	230 / 1	10,7	N/R	168	144	118	46	37	16	6	28	1
	WS102M-32	620208	2" F	1	230 / 3	4,6	N/R	168	144	118	46	37	16	6	29	1
WS102H	WS102HM-12	620258	2" F	1	230 / 1	13,3	N/R	190	170	148	100	48	20,8	9	28	1
18S	18S-CIM	520302	3" F	1,5	200 / 3	13,5	N/R	160	150	140	111	64	27,7	6	44	1
	18S-CIM	520301	3" F	1,5	230 / 1	15,5	N/R	160	150	140	111	64	27,7	6	44	1
	18S-CIM	520303	3" F	1,5	230 / 3	11,5	N/R	160	150	140	111	64	27,7	6	42	1
	18S-CIM	520304	3" F	1,5	460 / 3	5,3	N/R	160	150	140	111	64	27,7	6	42	1
20S	20S-CIM	520125	3" F	2	200 / 3	14,5	N/R	205	190	168	140	77	33,3	6	44	1
	20S-CIM	520100	3" F	2	230 / 1	18	N/R	205	190	168	140	77	33,3	6	44	1
	20S-CIM	520150	3" F	2	230 / 3	12,6	N/R	205	190	168	140	77	33,3	6	44	1
	20S-CIM	520175	3" F	2	460 / 3	6,1	N/R	205	190	168	140	77	33,3	6	44	1
Trituradora	GP-A231-20	520875	1 1/4" F	2	230 / 1	13,9	N/R	N/R	N/R	32	32	130	56	5	45	1

Aplicaciones

