



Encapsulados Sand Fighter™ / Ac. Inox. 316

Encapsulados - Trifásicos 6"

HP	Volts	Cable	Descripción	Corriente (Amps)	Consumo (kWh)	Eficiencia (%)	Amp. Rotor Bloqueado (Amps)	No. de Parte
7,5	230	3 DOL	SELLO SAND FIGHTER - C-SUBTROL	21,8	7	80	130	2366018120
	460			10,9	7	80	65	2366118120
10	200			32,7	9,4	79	198	2366528120
	230			28,4	9,4	79	172	2366028120
15	460			14,2	9,4	79	86	2366128120
	200			54,4	13,7	81	306	2366538120
20	230			41,6	13,7	81	266	2366038120
	460			20,8	13,7	81	133	2366138120
25	200			61,9	18,1	82	416	2366548120
	230			53,8	18,1	82	362	2366048120
30	460			26,9	18,1	82	181	2366148120
	200			77,1	22,5	83	552	2367658120
35	230	67	22,5	83	480	2367258120		
	460	33,5	22,5	83	240	2367158120		
40	230	79	26,9	83	568	2367268120		
	460	39,5	26,9	83	284	2367168120		
50	230	-	35,6	83	397	2367278125		
	460	54,9	35,6	83	397	2367178125		
60	460	67,7	45,1	82	414	2367188125		
75	460	81,0	53,5	84	518	2367198125		

NOTAS: Para motores arranque estrella triángulo, consultar fábrica.

